



# CS1311 Solid State Drive



### Performance

Transfer speed faster than a traditional HDD



### Enhanced Reliability

Non-volatile NAND up to 30 times more robust than HDDs



### Compatibility & Ease of Use

Ideal solution for a hard drive replacement in both MAC and PC systems

## CS1311 SOLID STATE DRIVES

The PNY CS1311 2.5-inch SATA-III (6 Gb/s) solid-state drive (SSD) is the mainstream performance line of PNY SSDs. It is an excellent choice for an upgrade from a hard disk drive (HDD). The PNY CS1311 was designed to be an easy and cost-effective HDD replacement for your existing PC system, without having to sacrifice performance. Upgrading to the CS1311 SSD will help you experience an overall performance boost. Boot up, power down, and load applications in seconds. With no moving parts, the PNY CS1311 is highly durable and includes a 3-year limited warranty.\*

The PNY CS1311 is an excellent choice for energy efficiency and consumes significantly less power than hard drives. Users can benefit from lower power usage, longer battery life, and a cooler, quieter system. Spend more time enjoying your system and less time worrying about battery consumption. The CS1311 lineup is available in a range of capacities from 120GB to 2TB.

The PNY CS1311 is engineered with the same level of quality and durability that our consumers have enjoyed with the CS900 SSDs. We've taken the world's most advanced NAND flash and refined the CS1311 to achieve a higher threshold for endurance and reliability. PNY's extensive testing and rigorous validation process ensures compatibility across various platforms and multiple operating systems.

### APPLICATIONS

- Mainstream SSD for PC upgrade
- Cost effective HDD replacement for better overall performance

### FEATURES AND BENEFITS

- Sequential Read of up to 550MB/s and Write of up to 530MB/s
- Faster boot up and quicker application launch
- Better overall system performance
- Reliable storage
- Low power consumption, cool and quiet operation

## PRODUCT SPECIFICATIONS

NAND Components	3D TLC Flash Memory
Interface	SATA-III (6 Gb/s); Backwards compatible with SATA-II
Form Factor	2.5-inch

### PERFORMANCE (MAX SEQUENTIAL READ/WRITE)

120GB	550 MB/s (Read), 510 MB/s (Write)
240GB	550 MB/s (Read), 520 MB/s (Write)
480GB	550 MB/s (Read), 520 MB/s (Write)
960GB	550 MB/s (Read), 520 MB/s (Write)
2TB	550 MB/s (Read), 530 MB/s (Write)

### POWER

Sata Link Power Management	Idle, Partial, Slumber
----------------------------	------------------------

### ENVIRONMENTAL

Power Island Support	Power Efficiency Management System
Operating Temperature	0°C ~ 70°C
Storage Temperature	-40°C ~ 85°C

### RELIABILITY / SECURITY

Certifications	BSMI, CE, EMC, FCC, KCC, REACH, RoHS, VCCI
Mean Time Between Failures (MTBF)	2,000,000 Hours
Error Correction Code	Up to 120 bits per 2K sector
Secure Erase	Standard, Enhanced Secure Erase
Product Health Monitoring	Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T)
Full End-to-End Data path protection	Supported

### COMPATIBILITY

RAID (0/1)	Supported
Serial ATA	Fully compliant with SATA-IO: Serial ATA Revision 3.0, ATA ATAPI-8 Standard Native Command Queuing (NCQ)

### ADDITIONAL FEATURES

Operating Systems	Windows 10, Windows 8, Windows 7, Windows Vista™, Windows XP™, Linux, Mac OS X, Ubuntu 14
Performance Optimization	TRIM (requires OS support)

## PRODUCT INFORMATION

Service & Support	3-Year Limited Warranty*
Usable Capacities (IDEMA)	120GB, 240GB, 480GB, 960GB, 2TB
PNY Part Number	120GB: SSD7CS1311-120-RB 240GB: SSD7CS1311-240-RB 480GB: SSD7CS1311-480-RB 960GB: SSD7CS1311-960-RB 2TB: SSD7CS1311-2TB-RB
Box Dimensions	3.94" x 5.13" x 0.63"
Dimensions (L x W x H)	3.9" x 2.75" x 0.25"
Weight	45g

\*For warranty details please see [www.pny.com](http://www.pny.com).